

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 10/06/2019 Revision date: 17/07/2019 Supersedes: 10/06/2019 Version: 2.0

ES-5630

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixtures

Product name : JECS PHENOL/PARABEN SYRINGE STANDARD (D, 98%) IN METHANOL-OD

Product code : ES-5630

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use

Industrial/Professional use spec : For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Cambridge Isotope Laboratories, Inc.

50 Frontage Road Andover, MA 01810

USA

USA: 1-800-322-1174 Int: 1-978-749-8000 <u>cilsales@isotope.com</u> www.isotope.com

Emergency telephone number

Emergency numbers:

Chemtrec: 1-800-424-9300 (24 hours) International: 1-703-741-5970 (24 hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225
Acute Tox. 3 (Oral) H301
Acute Tox. 3 (Dermal) H311
Acute Tox. 3 (Inhalation:vapour) H331
Skin Irrit. 2 H315
Eye Irrit. 2A H319
STOT SE 1 H370

Full text of hazard classes and H-statements : see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

F; R11

T; R39/23/24/25 Xi; R36/38

Full text of R-phrases: see section 16

GHS-US classification

Flam. Liq. 2 H225
Acute Tox. 3 (Oral) H301
Acute Tox. 3 (Dermal) H311
Acute Tox. 3 (Inhalation:vapour) H331
Skin Irrit. 2 H315
Eye Irrit. 2A H319
STOT SE 1 H370
Full text of H statements : see section 16

17/07/2019 EN (English US) 1/17

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Adverse physicochemical, human health and environmental effects

Eyes, Kidney, Liver, Heart, Central nervous system. Highly flammable liquid and vapor. Causes damage to organs (eyes, kidneys, liver, heart, central nervous system) (if inhaled, if swallowed, in contact with skin). Toxic in contact with skin. Toxic if inhaled. Toxic if swallowed. Causes skin irritation. Causes serious eye irritation.

2.2. Label elements

Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)







Signal word (CLP) : Danger

Hazard statements (CLP) : H225 - Highly flammable liquid and vapor

H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled

H315 - Causes skin irritation H319 - Causes serious eye irritation

H370 - Causes damage to organs (eyes, heart, kidneys, liver, central nervous system) (in

contact with skin, if inhaled, if swallowed)

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof electrical, lighting, ventilating equipment P260 - Do not breathe dust, mist, vapors, fume, gas, spray. P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area.

GHS-US labeling

Hazard pictograms (GHS-US)







Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H225 - Highly flammable liquid and vapor

H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled

H315 - Causes skin irritation H319 - Causes serious eye irritation

H370 - Causes damage to organs (eyes, kidneys, liver, heart, central nervous system) (Dermal,

Inhalation, oral)

Precautionary statements (GHS-US) : P210 - Keep away from heat, open flames, sparks. - No smoking.

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment

P241 - Use explosion-proof electrical, lighting, ventilating equipment

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.
P260 - Do not breathe dust, fume, mist, gas, spray, vapors.
P261 - Avoid breathing dust, fume, gas, spray, vapors, mist.
P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.

P271 - Use only outdoors or in a well-ventilated area P280 - Wear protective clothing, protective gloves.

P301+P310 - If swallowed: Immediately call a doctor, a POISON CENTER

P302+P352 - If on skin: Wash with plenty of water

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing P307+P311 - If exposed: Call a poison center/doctor

17/07/2019 EN (English US) 2/17

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P311 - Call a doctor, a POISON CENTER

P312 - Call a doctor, a POISON CENTER if you feel unwell

P321 - Specific treatment (see Hazardous component(s) for labeling on this label)

P322 - Specific treatment (see Hazard pictograms (CLP) on this label)

P330 - Rinse mouth.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P361+P364 - Take off immediately all contaminated clothing and wash it before reuse.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P370+P378 - In case of fire: Use alcohol resistant foam, carbon dioxide (CO2), dry

extinguishing powder to extinguish.

Product identifier

P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

Classification according to

2.3. Other hazards

PBT: not relevant - no registration required

SECTION 3: Composition/Information on ingredients

3.1. **Substances**

Not applicable

Name

Mixtures

Name	Product identifier	70	Directive 67/548/EEC
METHANOL-OD (D, 99%)	(CAS-No.) 1455-13-6 (EC-No.) 215-933-0 (EC Index-No.) 603-001-00-X (Unlabeled) (REACH-no) 01-2119433307-44	99.998985	F; R11 T; R39/23/24/25 Xi; R36/38
P-N-NONYLPHENOL (RING-D4,OD, 98%) substance listed as REACH Candidate (4-Nonylphenol, branched and linear [substances with a linear and/or branched alkyl chain with a carbon number of 9 covalently bound in position 4 to phenol, covering also UVCB- and well-defined substances which include any of the individual isomers or a combination thereof])	(CAS-No.) 358730-95-7 (EC-No.) 203-199-4	0.000308	Repr.Cat.3; R62 Repr.Cat.3; R63 Xn; R22 C; R34 N; R50/53
BISPHENOL F (D10, 98%)	(CAS-No.) 1794786-93-8 (EC-No.) 210-658-2 (Unlabeled)	0.000308	Xi; R36/37/38
BISPHENOL A (RING-3,3',5,5'-D4, 97%)	(CAS-No.) 80-05-7 (Unlabeled) (EC-No.) 201-245-8 (Unlabeled) (EC Index-No.) 604-030-00-0 (Unlabeled)	0.000308	Xn; R21/22 Xi; R37 R43 Xi; R41 Repr.Cat.3; R62 Repr.Cat.3; R63
METHYL PARABEN (METHYL 4-HYDROXYBENZOATE) (2,3,5,6-D4, 98%)	(CAS-No.) 362049-51-2 (EC-No.) 202-785-7	0.000031	R52/53
BISPHENOL S (2,2',3,3',5,5',6,6'-D8, 98%)	(CAS-No.) 80-09-1 (Unlabeled) (EC-No.) 201-250-5 (Unlabeled)	0.000031	Xn; R22 Xi; R36 Xi; R37
N-PROPYL PARABEN (N-PROPYL 4-HYDROXYBENZOATE) (2,3,5,6-D4, 98%)	(CAS-No.) 1219802-67-1	0.000031	Not classified
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
METHANOL-OD (D, 99%)	(CAS-No.) 1455-13-6 (EC-No.) 215-933-0 (EC Index-No.) 603-001-00-X (Unlabeled) (REACH-no) 01-2119433307-44	99.998985	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 1, H370
P-N-NONYLPHENOL (RING-D4,OD, 98%) substance listed as REACH Candidate (4-Nonylphenol, branched and linear [substances with a linear and/or branched alkyl chain with a carbon number of 9 covalently bound in position 4 to phenol, covering also UVCB- and well-defined substances which include any of the individual isomers or a combination thereof])	(CAS-No.) 358730-95-7 (EC-No.) 203-199-4	0.000308	Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400
BISPHENOL F (D10, 98%)	(CAS-No.) 1794786-93-8 (EC-No.) 210-658-2 (Unlabeled)	0.000308	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335

17/07/2019 3/17 EN (English US)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
BISPHENOL A (RING-3,3',5,5'-D4, 97%)	(CAS-No.) 80-05-7 (Unlabeled) (EC-No.) 201-245-8 (Unlabeled) (EC Index-No.) 604-030-00-0 (Unlabeled)	0.000308	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 2, H361 STOT SE 3, H335
METHYL PARABEN (METHYL 4-HYDROXYBENZOATE) (2,3,5,6-D4, 98%)	(CAS-No.) 362049-51-2 (EC-No.) 202-785-7	0.000031	Aquatic Chronic 3, H412
BISPHENOL S (2,2',3,3',5,5',6,6'-D8, 98%)	(CAS-No.) 80-09-1 (Unlabeled) (EC-No.) 201-250-5 (Unlabeled)	0.000031	Eye Irrit. 2, H319 STOT SE 3, H335
N-PROPYL PARABEN (N-PROPYL 4-HYDROXYBENZOATE) (2,3,5,6-D4, 98%)	(CAS-No.) 1219802-67-1	0.000031	Not classified

Name	Product identifier	%	GHS-US classification
METHANOL-OD (D, 99%)	(CAS-No.) 1455-13-6	99.998985	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 1, H370
P-N-NONYLPHENOL (RING-D4,OD, 98%)	(CAS-No.) 358730-95-7	0.000308	Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400
BISPHENOL F (D10, 98%)	(CAS-No.) 1794786-93-8	0.000308	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
BISPHENOL A (RING-3,3',5,5'-D4, 97%)	(CAS-No.) 80-05-7 (Unlabeled)	0.000308	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 2, H361 STOT SE 3, H335 Aquatic Acute 2, H401
METHYL PARABEN (METHYL 4-HYDROXYBENZOATE) (2,3,5,6-D4, 98%)	(CAS-No.) 362049-51-2	0.000031	Aquatic Acute 3, H402 Aquatic Chronic 3, H412
BISPHENOL S (2,2',3,3',5,5',6,6'-D8, 98%)	(CAS-No.) 80-09-1 (Unlabeled)	0.000031	Eye Irrit. 2A, H319 STOT SE 3, H335
N-PROPYL PARABEN (N-PROPYL 4-HYDROXYBENZOATE) (2,3,5,6-D4, 98%)	(CAS-No.) 1219802-67-1	0.000031	Aquatic Acute 2, H401

Full text of R- and H- phrases: see section 16

SECTION 4: First aid measures

Description of first aid measures

First-aid measures general If medical advice is needed, have product container or label at hand. Call a physician

immediately. Evacuate danger area.

Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial First-aid measures after inhalation

respiration. Call a doctor.

First-aid measures after skin contact Rinse skin with water/shower. Take immediately victim to hospital. Remove/Take off

immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth.

First-aid measures after ingestion Call a physician immediately.

Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Toxic if inhaled.

Symptoms/effects after skin contact Toxic in contact with skin. Symptoms/effects after eye contact : Causes serious eve irritation.

Symptoms/effects after ingestion : Toxic if swallowed.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

17/07/2019 EN (English US) 4/17

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry powder. Dry sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapor.

Reactivity : Vapors may form flammable mixture with air. Highly flammable liquid and vapor.

5.3. Advice for firefighters

Firefighting instructions : Do not enter fire area without proper protective equipment, including respiratory protection.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing. Wear recommended personal protective equipment.

Other information : Use water spray to cool exposed surfaces.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures

: Wear respiratory protection. Do not breathe dust, mist, gas, spray, vapors, fume. Avoid contact with skin, eyes and clothing. Ventilate spillage area. Remove all sources of ignition. No open flames, no sparks, and no smoking. Ensure adequate air ventilation. Special attention should be given to low areas/pits where flammable vapors can accumulate.

6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Prevent entry to sewers and public waters. Do not allow to enter drains or water courses. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment

: Dike and contain spill.

Methods for cleaning up

: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. This material and its container must be disposed of in a safe way, and as per local legislation.

Other information

: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe dust, fume, gas, spray, vapors, mist. Do not get in eyes, on skin, or on clothing. Use only outdoors or in a well-ventilated area.

Hygiene measures

: Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

Storage conditions

: Ground/bond container and receiving equipment. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

: Store at room temperature away from light and moisture.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

JECS PHENOL/PARABEN SY	YRINGE STANDARD (D, 98%) IN METHANOL-OD	
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.00000000 ppm Basis: USA. ACGIH Threshold
		Limit Values (TLV)

17/07/2019 EN (English US) 5/17

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	YRINGE STANDARD (D, 98%) IN METHANOL-OD	
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	250 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Headache. Nausea. Dizziness. Eye damage. Substances for which there is a Biological Exposure Index or Indices (see BEI section). Danger of cutaneous absorption.
USA NIOSH	NIOSH REL (TWA) (mg/m³)	260 mg/m³ Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (mg/m³)	325 mg/m³ Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm Basis: NIOSH Recommended Exposure Limits
USA NIOSH	Remark (NIOSH)	Potential for dermal absorption.
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m³ Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (STEL) (mg/m³)	325 mg/m³ Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (STEL) (ppm)	250 ppm Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (Ceiling) (ppm)	1000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	Remark (OSHA)	The value in mg/m3 is approximate. Skin notation.
METHANOL-OD (D, 99%) (14	55-13-6)	
Italy - Portugal - USA ACGIH		200.00000000 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	250 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Headache. Nausea. Dizziness. Eye damage. Substances for which there is a Biological Exposure Index or Indices (see BEI section). Danger of cutaneous absorption.
USA NIOSH	NIOSH REL (TWA) (mg/m³)	260 mg/m³ Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (mg/m³)	325 mg/m³ Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm Basis: NIOSH Recommended Exposure Limits
USA NIOSH	Remark (NIOSH)	Potential for dermal absorption.
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m³ Basis: USA. Occupational Exposure Limit: (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)

17/07/2019 EN (English US) 6/17

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

METHANOL-OD (D, 99%) (1455-13-6)		
USA OSHA	OSHA PEL (STEL) (mg/m³)	325 mg/m³ Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (STEL) (ppm)	250 ppm Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (Ceiling) (ppm)	1000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	Remark (OSHA)	The value in mg/m3 is approximate. Skin notation.

JECS PHENOL/PARABEN SYRINGE STANDARD (D, 98%) IN METHANOL-OD	
DNEL/DMEL (Workers)	
Acute - systemic effects, dermal	40 mg/kg bodyweight/day
Acute - systemic effects, inhalation	260 mg/m³
Acute - local effects, dermal	260 mg/cm ²
Long-term - systemic effects, dermal	40 mg/kg bodyweight/day
Long-term - local effects, dermal	260 mg/cm ²
Long-term - local effects, inhalation	260 mg/m³
DNEL/DMEL (General population)	
Acute - systemic effects, dermal	8 mg/kg body weight
Acute - systemic effects, inhalation	50 mg/m³
Acute - systemic effects, oral	8 mg/kg body weight
Acute - local effects, inhalation	50 mg/m³
Long-term - systemic effects,oral	8 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	50 mg/m³
Long-term - systemic effects, dermal	8 mg/kg bodyweight/day
Long-term - local effects, inhalation	50 mg/m³
PNEC (Water)	
PNEC aqua (freshwater)	154 mg/l
PNEC aqua (marine water)	15.4 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	570.4 mg/kg dwt
PNEC (Soil)	
PNEC soil	23.5 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	100 mg/kg

Exposure controls

Appropriate engineering controls : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Personal protective equipment : Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.









Materials for protective clothing

Hand protection : Wear suitable protective clothing and gloves.

Eye protection : Wear eye protection. Chemical goggles or face shield with safety glasses.

Skin and body protection : Wear suitable protective clothing, gloves and eye/face protection.

: In case of inadequate ventilation wear respiratory protection. Approved supplied air respirator. Respiratory protection

Environmental exposure controls : Avoid release to the environment.

17/07/2019 EN (English US) 7/17

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

The properties listed below are for the solvent, the main component of this mixture.

Physical state : Liquid

Appearance : Liquid

Molecular mass : 33.05 g/mol (Labeled)

Color : Colorless
Odor : Pungent

Odor threshold : No data available pH : No data available Relative evaporation rate (butyl acetate=1) : No data available Melting point : -98 °C (-144 °F) Freezing point : No data available Boiling point : 64.7 °C (148.5 °F)

Flash point : 9.7 °C (49.5 °F) - closed cup

Auto-ignition temperature : 455 °C (851 °F) at 1,013 hPa (760 mmHg)

Decomposition temperature : No data available Flammability (solid, gas) : No data available

Vapor pressure : 130.3 hPa (97.7 mmHg) at 20 °C (68 °F); 169.27 hPa (126.96 mmHg) at 25 °C (77 °F)

Vapor pressure at 50 °C : 546.6 hPa (410.0 mmHg) at 50 °C (122 °F)

Relative vapor density at 20 °C : 1.11

Relative density : No data available

Specific gravity / density : 0.791 g/ml at 25 °C (77 °F)
Solubility : Water: Completely miscible

Log Pow : -0.77

Log Kow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : Not explosive.

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Explosion limits : 6 - 36 % (V)

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapors may form flammable mixture with air. Highly flammable liquid and vapor.

10.2. Chemical stability

See storage and expiration date on CoA.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Acid anhydrides. Acid chlorides. Oxidizing agent. Alkali Metal Amides. Reducing agents. Acids.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO2).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Toxic if swallowed. Dermal: Toxic in contact with skin. Inhalation:vapour: Toxic if inhaled.

JECS PHENOL/PARABEN SYRINGE STANDARD (D, 98%) IN METHANOL-OD	
LD50 oral rat	1187 - 2769 mg/kg
LD50 dermal rabbit	17100 mg/kg

17/07/2019 EN (English US) 8/17

Safety Data Sheet

Aspiration hazard

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

JECS PHENOL/PARABEN SYRINGE STANDA	JECS PHENOL/PARABEN SYRINGE STANDARD (D, 98%) IN METHANOL-OD		
LC50 inhalation rat (mg/l)	128.2 mg/l/4h; 87.6 mg/l - 6 h		
ATE CLP (oral)	100.000 mg/kg body weight		
ATE CLP (dermal)	300.000 mg/kg body weight		
ATE CLP (vapors)	3.000 mg/l/4h		
ATE CLP (dust, mist)	128.200 mg/l/4h		
LDLO, oral, human	143 mg/kg Remarks: Lungs, Thorax, or Respiration: Dyspnea. Ingestion may cause		
-,,	gastrointestinal irritation, nausea, vomiting and diarrhea.		
METHANOL-OD (D, 99%) (1455-13-6)			
LD50 oral rat	1187 - 2769 mg/kg		
LD50 dermal rabbit	17100 mg/kg		
LC50 inhalation rat (mg/l)	128.2 mg/l/4h ; 87.6 mg/l - 6 h		
ATE CLP (oral)	100.000 mg/kg body weight		
ATE CLP (dermal)	300.000 mg/kg body weight		
ATE CLP (vapors)	3.000 mg/l/4h		
ATE CLP (dust, mist)	128.200 mg/l/4h		
LDLO, oral, human	143 mg/kg Remarks: Lungs, Thorax, or Respiration: Dyspnea. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.		
METHYL PARABEN (METHYL 4-HYDROXYBI	ENZOATE) (2,3,5,6-D4, 98%) (362049-51-2)		
LD50 oral rat	2100 mg/kg (OCED Test Guideline 401)		
ATE CLP (oral)	2100.000 mg/kg body weight		
P-N-NONYLPHENOL (RING-D4,OD, 98%) (358	3730-95-7)		
LD50 oral rat	1620 mg/kg		
ATE CLP (oral)	1620.000 mg/kg body weight		
, ,			
BISPHENOL S (2,2',3,3',5,5',6,6'-D8, 98%) (80- LD50 oral rat			
LD50 drai rat LD50 dermal rabbit	4556 mg/kg		
	> 10250 mg/kg		
ATE CLP (oral)	4556.000 mg/kg body weight		
BISPHENOL F (D10, 98%) (1794786-93-8)	1.000		
LD50 oral rat	4950 mg/kg		
ATE CLP (oral)	4950.000 mg/kg body weight		
BISPHENOL A (RING-3,3',5,5'-D4, 97%) (80-0			
LD50 oral rat	> 2,000 - 5,000 mg/kg - male and female - (OECD Test Guideline 401)		
LD50 dermal rabbit	3000 mg/kg		
ATE CLP (oral)	500.000 mg/kg body weight		
ATE CLP (dermal)	1100.000 mg/kg body weight		
N-PROPYL PARABEN (N-PROPYL 4-HYDRO	XYBENZOATE) (2,3,5,6-D4, 98%) (1219802-67-1)		
LD50 oral rat	> 5000 mg/kg (OECD Test Guideline 401)		
Skin corrosion/irritation	: Skin. rabbit. Result: No skin irritation		
Serious eye damage/irritation	: Eyes. rabbit. Result: No eye irritation		
Respiratory or skin sensitization	: Maximisation Test . Guinea pig. Did not cause sensitization. (OECD 406 method)		
Germ cell mutagenicity	: AMES test: S. tymphimurium. Result: negative. fibroblast. Result: Negative. Mutation in mammalian somatic cells. Mutagenicity (in vivo mammalian bone-marrow cystogenetic test, chromosomal analysis) - Mouse - male and female Result: negative. Mouse - male and female. Result: Negative		
Carcinogenicity	: Not classified		
Reproductive toxicity	: Damage to fetus not classifiable. Fertility classification not possible from current data.		
Specific target organ toxicity – single exposure	: Causes damage to organs through prolonged or repeated exposure		
Specific target organ toxiony only oxposure	Causes damage to organs		
Specific target organ toxicity – repeated exposure	: The substance or mixture is not classified as specific target organ toxicant, repeated exposure. No data available		
BISPHENOL A (RING-3,3',5,5'-D4, 97%) (80-0	5-7 (Unlabeled))		

17/07/2019 EN (English US) 9/17

: No aspiration toxicity classification.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Potential Adverse human health effects and symptoms

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Effects due to Ingestion may include: Headache. Dizziness. Drowsiness. metabolic acidosis. Coma. May be fatal if swallowed and enters airways. If swallowed there is a risk of blindness. Effects on humans.

stomach.

Symptoms/effects after inhalation : Toxic if inhaled.

Symptoms/effects after skin contact : Toxic in contact with skin. Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : Toxic if swallowed.

SECTION 12: Ecological information

Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse

effects in the environment.		
JECS PHENOL/PARABEN SYRINGE STANDARD (D, 98%) IN METHANOL-OD		
15400 mg/l mortality LC50 - Lepomis machrochirus (Bluegill) - 96 h		
> 10000 mg/l Daphnia magna (Water flea) - 48 h		
22000 mg/l Growth inhibition EC50 - Scenedesmus capricornutum (fresh water algae) - 96 h		
7900 mg/l Oryzias latipes - 200 h		
METHANOL-OD (D, 99%) (1455-13-6)		
15400 mg/l mortality LC50 - Lepomis machrochirus (Bluegill) - 96 h		
> 10000 mg/l Daphnia magna (Water flea) - 48 h		
22000 mg/l Growth inhibition EC50 - Scenedesmus capricornutum (fresh water algae) - 96 h		
7900 mg/l Oryzias latipes - 200 h		
METHYL PARABEN (METHYL 4-HYDROXYBENZOATE) (2,3,5,6-D4, 98%) (362049-51-2)		
59.5 mg/l Oryzias latipes - 96 h		
41.1 mg/l Daphnia magna (water flea) - 48 h		

WEITIL PARABEN (WEITIL 4-HIDROATBENZOATE) (2,3,3,0-04, 30%) (302043-31-2)	
LC50 fish 1	59.5 mg/l Oryzias latipes - 96 h
EC50 Daphnia 1	41.1 mg/l Daphnia magna (water flea) - 48 h
P.N. NONVI DUENOI (PING. DA OD. 00%) (250720.05.7)	

P-N-NONYLPHENOL (RING-D4,OD, 98%) (358730-95-7)	
LC50 fish 1	1.4 mg/l Pimephales promels (fathead minnow) - 96 h
EC50 Daphnia 1	0.18 mg/l Daphnia magna (Water flea) - 24 h
ErC50 (algae) 0.243 mg/l Algae - 4 Months	

BISPHENOL A (RING-3,3',5,5'-D4, 97%) (80-05-7 (Unlabeled))			
LC50 fish 1 4.6 mg/l Pimephales promelas (fathead minnow) - 96 h			
EC50 Daphnia 1	3.9 mg/l Daphnia magna (Water Flea) - 48 h		

N-PROPYL PARABEN (N-PROPYL 4-HYDROXYBENZOATE) (2,3,5,6-D4, 98%) (1219802-67-1)			
LC50 fish 1 6.4 mg/l Danio rerio - 96 h (OECD Test Guideline 203)			
EC50 Daphnia 1	15.4 mg/l Daphnia magna - 48 h (ISO 6341)		
EC50 other aquatic organisms 1 7.6 mg/l Pseudokirchneriella subcapitata - 72 h (OECD Test Guideline 201)			

12.2. Persistence and degradability

JECS PHENOL/PARABEN SYRINGE STANDARD (D, 98%) IN METHANOL-OD			
Biochemical oxygen demand (BOD)	600 - 1200 mg/g		
Chemical oxygen demand (COD)	1420 mg/g		
ThOD	1500 mg/g		
Biodegradation	72 % - rapidly biodegradable aerobic - Exposure time 5 d		
METHANOL-OD (D, 99%) (1455-13-6)			
Biochemical oxygen demand (BOD)	600 - 1200 mg/g		
Chemical oxygen demand (COD)	1420 mg/g		
ThOD	1500 mg/g		
Biodegradation	72 % - rapidly biodegradable aerobic - Exposure time 5 d		
METHYL PARABEN (METHYL 4-HYDROXYBENZOATE) (2,3,5,6-D4, 98%) (362049-51-2)			
Persistence and degradability	Biodegradability: Result: 89 % - Readily biodegradable. Aerobic - exposure time: 28 d.		
BISPHENOL A (RING-3,3',5,5'-D4, 97%) (80-05-7 (Unlabeled))			
Biodegradation	89 % aerobic - Exposure time 28 d Readily biodegradable - (OECD Test Guideline 301F)		

17/07/2019 EN (English US) 10/17

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

, ,				
N-PROPYL PARABEN (N-PROPYL 4-HYDRO	DXYBENZOATE) (2,3,5,6-D4, 98%) (1219802-67-1)			
Biodegradation	Result: - Readily biodegradable			
12.3. Bioaccumulative potential				
JECS PHENOL/PARABEN SYRINGE STANDARD (D, 98%) IN METHANOL-OD				
BCF fish 1	5 mg/l Cyprinus carpio (Carp) - 72 d at 20 °C			
Bioconcentration factor (BCF REACH)	1			
Log Pow	-0.77			
METHANOL-OD (D, 99%) (1455-13-6)				
BCF fish 1	5 mg/l Cyprinus carpio (Carp) - 72 d at 20 °C			
Bioconcentration factor (BCF REACH)	1			
Log Pow	-0.77			
METHYL PARABEN (METHYL 4-HYDROXYE	BENZOATE) (2,3,5,6-D4, 98%) (362049-51-2)			
Log Pow	1.98			
Bioaccumulative potential	No data available.			
P-N-NONYLPHENOL (RING-D4,OD, 98%) (35	58730-95-7)			
Bioconcentration factor (BCF REACH)	1300			
Log Pow	5.76			
Bioaccumulative potential	Gasterosteus aculeatus - 16 d.			
BISPHENOL A (RING-3,3',5,5'-D4, 97%) (80-	05-7 (Unlabeled))			
BCF fish 1	0.015 mg/l Cyprinus carpio (Carp) - 42 d			
Bioconcentration factor (BCF REACH)	0 20 - 67			
Log Pow	3.4 at 21.5 °C (70.7 °F)			
N-PROPYL PARABEN (N-PROPYL 4-HYDRO	DXYBENZOATE) (2,3,5,6-D4, 98%) (1219802-67-1)			
Log Pow	2.5 - 3			
12.4. Mobility in soil				
JECS PHENOL/PARABEN SYRINGE STAND	ARD (D, 98%) IN METHANOL-OD			
Ecology - soil Not degradable in the soil.				
METHANOL-OD (D, 99%) (1455-13-6)				
Ecology - soil	Not degradable in the soil.			
METHYL PARABEN (METHYL 4-HYDROXYBENZOATE) (2,3,5,6-D4, 98%) (362049-51-2)				
Ecology - soil	No data available.			
BISPHENOL A (RING-3,3',5,5'-D4, 97%) (80-05-7 (Unlabeled))				
Ecology - soil	Not available.			
12.5. Results of PBT and vPvB assessme				
PBT: not relevant – no registration required				
METHANOL-OD (D, 99%) (1455-13-6) PBT: not relevant – no registration required				
P-N-NONYLPHENOL (RING-D4,OD, 98%) (358730-95-7) This substance/mixture does not meet the PBT criteria of REACH, annex XIII				
This substance/mixture does not meet the vPvB criteria of REACH, annex XIII				
·				
12.6. Other adverse effects				

12.6. Other adverse effects

Other adverse effects : Avoid release to the environment.

Other information : Stability in water: at 19 °C - (83 - 91%) - 72 h. Remarks: Hydrolyses on contact with water.

Hydrolyses readily.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

No additional information available

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14	.1.	U	N	ทเ	ım	b	er

UN-No.(DOT) : 1230 DOT NA no. UN1230

17/07/2019 EN (English US) 11/17

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

UN proper shipping name 14.2.

Proper Shipping Name (DOT)

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) 3 - Flammable liquid

6.1 - Poison





DOT Symbols

+ - Fixes (cannot be altered) proper shipping name, hazard class, and packing group, I - Proper

shipping name appropriate for international and domestic transportation

Packing group (DOT)

II - Medium Danger

DOT Special Provisions (49 CFR 172.102)

: IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150 DOT Packaging Non Bulk (49 CFR 173.xxx) : 202 DOT Packaging Bulk (49 CFR 173.xxx) : 242 **DOT RQ** : 5000 lbs Marine pollutant : No

Additional information

Emergency Response Guide (ERG) Number : 131

Other information : No supplementary information available.

Overland transport

Packing group (ADR) : 11

Class (ADR) : 3 - Flammable liquid

Hazard identification number (Kemler No.) : 336 Classification code (ADR)

Hazard labels (ADR) : 3 - Flammable liquids

6.1 - Toxic substances



Orange plates

Tunnel restriction code (ADR) : D/E Limited quantities (ADR) 11 Excepted quantities (ADR) : E2

17/07/2019 EN (English US) 12/17

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transport by sea

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

MFAG-No : 131

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 1 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

Civil Aeronautics Law : Flammable liquids

14.4. Environmental hazards

Other information : No supplementary information available.

14.5. Special precautions for user

SARA Section 302 Threshold Planning

SARA Section 311/312 Hazard Classes

Quantity (TPQ)

14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

The state of the s				
JECS PHENOL/PARABEN SYRINGE STANDARD (D, 98%) IN METHANOL-OD				
Listed on the United States TSCA (Toxic Substances Control Act) inventory				
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporing requirements of the United States SARA Section 302.			
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard			
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313			
METHANOL-OD (D, 99%) (1455-13-6)				
Listed on the United States TSCA (Toxic Substa	nces Control Act) inventory			
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporing requirements of the United States SARA Section 302.			
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard			
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313			
METHYL PARABEN (METHYL 4-HYDROXYBE	ENZOATE) (2,3,5,6-D4, 98%) (362049-51-2)			
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302			
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313			
P-N-NONYLPHENOL (RING-D4,OD, 98%) (358	730-95-7)			
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302			
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard			
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313			
BISPHENOL S (2,2',3,3',5,5',6,6'-D8, 98%) (80-09-1 (Unlabeled))				
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302			
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard			
SARA Section 313 - Emission Reporting Not subject to reporting requirements of the United States SARA Section 313				
BISPHENOL F (D10, 98%) (1794786-93-8)				

17/07/2019 EN (English US) 13/17

Immediate (acute) health hazard

Not subject to reporting requirements of the United States SARA Section 302

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

BISPHENOL F (D10, 98%) (1794786-93-8)	
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313
BISPHENOL A (RING-3,3',5,5'-D4, 97%) (80-05-	7 (Unlabeled))
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313
N-PROPYL PARABEN (N-PROPYL 4-HYDROX	YBENZOATE) (2,3,5,6-D4, 98%) (1219802-67-1)
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313

15.2. International regulations

CANADA

JECS PHENOL/PARABEN SYRINGE STANDARD (D, 98%) IN METHANOL-OD

Listed on the Canadian DSL (Domestic Substances List)

METHANOL-OD (D, 99%) (1455-13-6)

Listed on the Canadian DSL (Domestic Substances List)

15.2.1. National regulations

No additional information available

15.3. US State regulations

15.3. US State regulations							
JECS PHENOL/PARABEN SYRINGE STANDARD (D, 98%) IN METHANOL-OD()							
U.S California - Proposition 65 - Carcinogens List		No					
U.S California - Propositi	on 65 - Developmental	Yes					
Toxicity							
U.S California - Propositi Toxicity - Female	on 65 - Reproductive	No					
U.S California - Propositi	on 65 - Reproductive	No					
Toxicity - Male	on oo reproductive	NO					
METHANOL-OD (D, 99%)							
U.S California -	U.S California -	U.S California -	U.S California -	No significant risk level			
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	(NSRL)			
Carcinogens List	Developmental Toxicity	Reproductive Toxicity - Female	Reproductive Toxicity - Male				

No	Yes	No	No				
METHYL PARABEN (MET	HYL 4-HYDROXYBENZOAT	TE) (2,3,5,6-D4, 98%) (362049-5	1-2)				
U.S California -	U.S California -	U.S California -	U.S California -	No significant risk level			
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	(NSRL)			
Carcinogens List	Developmental Toxicity	Reproductive Toxicity - Female	Reproductive Toxicity - Male				
No	No	No	No				
P-N-NONYLPHENOL (RIN	P-N-NONYLPHENOL (RING-D4,OD, 98%) (358730-95-7)						
U.S California -	U.S California -	U.S California -	U.S California -	No significant risk level			
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	(NSRL)			
Carcinogens List	Developmental Toxicity	Reproductive Toxicity -	Reproductive Toxicity -				
		Female	Male				
No	No	No	No				
BISPHENOL S (2,2',3,3',5,5',6,6'-D8, 98%) (80-09-1 (Unlabeled))							
U.S California -	U.S California -	U.S California -	U.S California -	No significant risk level			
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	(NSRL)			
Carcinogens List	Developmental Toxicity	Reproductive Toxicity - Female	Reproductive Toxicity - Male				
		Female	iviale				
47/07/0040				44/47			

17/07/2019 EN (English US) 14/17

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

BISPHENOL S (2,2',3,3',5,5',6,6'-D8, 98%) (80-09-1 (Unlabeled))				
No	No	No	No	
BISPHENOL F (D10, 98%)	(1794786-93-8)			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	
BISPHENOL A (RING-3,3',	5,5'-D4, 97%) (80-05-7 (Unlab	eled))		
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	Yes	No	
N-PROPYL PARABEN (N-PROPYL 4-HYDROXYBENZOATE) (2,3,5,6-D4, 98%) (1219802-67-1)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

METHYL PARABEN (METHYL 4-HYDROXYBENZOATE) (2,3,5,6-D4, 98%) (362049-51-2)

State or local regulations

- U.S. Pennsylvania RTK (Right to Know) List
- U.S. New Jersey Right to Know Hazardous Substance List

P-N-NONYLPHENOL (RING-D4,OD, 98%) (358730-95-7)

State or local regulations

- U.S. Pennsylvania RTK (Right to Know) List
- U.S. New Jersey Right to Know Hazardous Substance List

BISPHENOL S (2,2',3,3',5,5',6,6'-D8, 98%) (80-09-1 (Unlabeled))

State or local regulations

- U.S. Pennsylvania RTK (Right to Know) List
- U.S. New Jersey Right to Know Hazardous Substance List

BISPHENOL F (D10, 98%) (1794786-93-8)

State or local regulations

- U.S. Pennsylvania RTK (Right to Know) List
- U.S. New Jersey Right to Know Hazardous Substance List

BISPHENOL A (RING-3,3',5,5'-D4, 97%) (80-05-7 (Unlabeled))

State or local regulations

- U.S. Massachusetts Right To Know List
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. New Jersey Right to Know Hazardous Substance List

N-PROPYL PARABEN (N-PROPYL 4-HYDROXYBENZOATE) (2,3,5,6-D4, 98%) (1219802-67-1)

State or local regulations

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

SECTION 16: Other information

Other information

: This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R-, H- and EUH-phrases:

Acute Tox. 3 (Dermal) Acute toxicity (dermal) Category 3

17/07/2019 EN (English US) 15/17

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12 / Rules and Regulations	
Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Flam. Liq. 2	Flammable liquids Category 2
Repr. 2	Reproductive toxicity Category 2
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization, Category 1
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H335	May cause respiratory irritation
H361	Suspected of damaging fertility or the unborn child
H370	Causes damage to organs
H400	Very toxic to aquatic life
H412	Harmful to aquatic life with long lasting effects
R11	Highly flammable
R21/22	Harmful in contact with skin and if swallowed
R22	Harmful if swallowed
R34	Causes burns
R36	Irritating to eyes
R36/37/38	Irritating to eyes, respiratory system and skin
R36/38	Irritating to eyes and skin
R37	Irritating to respiratory system
R39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed
R41	Risk of serious damage to eyes
R43	May cause sensitization by skin contact
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R62	Possible risk of impaired fertility
R63	Possible risk of harm to the unborn child
C	Corrosive
F	Highly flammable
N	Dangerous for the environment
Т	Toxic
Xi	Irritant
Xn	Harmful

NFPA health hazard


: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard

: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.



17/07/2019 EN (English US) 16/17

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard Physical : 0 Minimal Hazard

CIL Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

17/07/2019 EN (English US) 17/17